

TRUBUILD PRIMESURE PREMIUM

Premium Quality Water Based Acrylic Primer



TECHNICAL DATA SHEET

VER NO.11

TRUBUILD PRIMESURE PREMIUM is an excellent water-based primer with good penetration and outstanding bond strength, which can be used on multiple surfaces like concrete, screed, cement sheet, glossed surface like china mosaic, tiles, etc, before application of protective water based top coats.

ADVANTAGES



EXCELLENT ADHESION



ECONOMICAL



GOOD PENETRATION



ENHANCED DURABILITY

- Economical
- Excellent adhesion on various substrates
- Reduces the chance of blister formation
- Can be used in both horizontal & vertical surfaces
- Good penetration
- Enhance the bonding and overall durability of the system




AREAS OF APPLICATION



APPLICATION AREAS

- Trubuild Primesure Premium as a primer can be used for different substrates like concrete, screed, cement sheet, glossed surface like china mosaic, ceramic tiles and vitrified tiles, etc.

AVAILABLE PACKING



HOW TO APPLY

Surface preparation:

The surface should be clean and dry before application of Trubuild Primesure Premium. It should be free from dust, unsound material, loose plaster, oil, paint, grease, algae and corrosion deposits. Fill all the cracks up to 5mm by Trubuild CFP 425 and for more than 5 mm, make PMM using Trubuild WPL 333/Trubuild BWP 222.

Application methodology:

Mix well after opening the container of Trubuild Primesure Premium before application. Then apply the Trubuild Primesure Premium by brush ensuring covering of all the waterproofing area where subsequent water-based top coats will come further. Leave it for 3-5 hours for air curing, then apply water based top coat.

TRUBUILD PRIMESURE PREMIUM

Premium Quality Water Based Acrylic Primer



TECHNICAL DATA SHEET
VER NO. 1.1

TECHNICAL DETAILS

PROPERTIES	STANDARD	RESULTS
Physical state	In house	Low viscous liquid
Appearance	Visual	Opaque
Colour	Visual	Yellow/white
pH	ASTM E70	7-8
Density, g/cc	ASTM D 1475-2013	1.01-1.03
Bond strength, on concrete, MPa	ASTM D 7234-2021	≥1.5
Bond strength, on vitrified tiles, MPa	ASTM D 7234-2021	≥2
Bond strength, on ceramic mat surface, MPa	ASTM D 7234-2021	≥2
Bond strength, on ceramic glaze surface, MPa	ASTM D 7234-2021	≥2

HANDLING PRECAUTIONS AND LIMITATIONS

- Trubuild Primesure Premium should not be diluted with water
- Trubuild Primesure Premium shall be applied to the substrate temp above 10°C to below 40°C
- Surface should be clean before application of water-based top coats
- Ensure to provide a protective water-based top coat over the final coat to ensure overall workability.
- Avoid coating during intermittent rain.
- Apply Trubuild Primesure Premium after cleaning of all types of dust and other contaminants like oil, grease, and other debris if present.
- Mandatory and recommended industrial hygiene procedures should be followed whenever our products are being handled and processed. For additional information please refer Material Safety Data Sheet.

STORAGE

Product should be stored in a dry place in its original, properly closed containers at temperatures between 2-40°C. Partially emptied container should be closed immediately.

COVERAGE

- 120-150 sqft./L/coat
- Depends upon the level and porosity of the substrate

SHELF LIFE

12 months from the date of manufacturing in a closed container

DISCLAIMER: This technical data sheet replaces all previous versions of it from the immediate effect. The information, and, in particular, the recommendations relating to the application and end-use of Astral Ltd, construction chemical products, are given in good faith based on our knowledge and experience of the products when properly stored, handled and applied under suitable favourable conditions in accordance with application instructions recommended in product technical data sheet. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. For the products on which company is offering warranty, please refer to warranty document to know entire terms and conditions. The same can be availed on request or from company website. The values mentioned in the above tables in technical data sheet are obtained in controlled lab conditions when tested properly by competent laboratory. Tolerance up to five to ten percentage on the lower side from the above values are allowable. Astral Ltd. reserves the right to change the properties of its products without notice. The end user of the product must test the product's suitability for the intended application and purpose. Astral Ltd will not bear any responsibilities on the product failure if it is wrongly positioned or if improper application methodology is adopted by the user or the applicator. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local product technical data sheet for the product concerned, copies of which will be supplied on request. No freedom from any patent owned by Seller or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, customer is responsible for determining whether products and the information in this document are appropriate for the customer's use and for ensuring that the customer's workplace, and disposal practices are in compliance with applicable laws and other governmental enactments.



ASTRAL LIMITED

CIN: U24295GJ2009PLC058120

Registered Office: 207/1, 'Astral House', B/h Rajpath Club, Off S.G. Highway, Ahmedabad-380059, Gujarat, India.

P: +91 79 6621 2000 | F: +91 79 6621 2121

E-mail: customercare@astraladhesives.com Website: www.trubuild.in