

TRUBUILD WRP 777

Water Repellent



TECHNICAL DATA SHEET

VER NO. 1.1

Trubuild WRP 777 (Water Repellent) is silane-based, non-flammable, water soluble solution designed to incorporate water repellence to varied surface like sand stone, marble, concrete, exposed bricks and terracotta tiles. It is used for waterproofing of most of the construction surfaces as it penetrates deeply in the surface and provides excellent water repellence without changing the appearance/colour of substrate.

Meets the requirement of IS: 12027: 1987.

ADVANTAGES



EASY TO USE



COST EFFECTIVE



HIGH PENETRATION



REDUCES EFFLORESCENCE

- Brushable and easy-to-use
- Trubuild WRP 777 is breathable, penetrable and supplied in a ready-to-use form
- Doesn't stain or change appearance/ colour of substrate
- Cost effective
- Waterproof for porous stone, concrete, plasters, etc.
- Due to low viscosity, penetration in substrate is very high
- Use of Trubuild WRP 777 reduces efflorescence, improves resistance to the effects of weathering and seals porous substrates against moisture.



AREAS OF APPLICATION



APPLICATIONS

- As a sealer for sand stone, concrete & marble surfaces
- Can be used on any porous substrate

Note-Before applying to any substrate, sampling should be done on a small patch, if no adverse effects are observed, use it on a large area.

AVAILABLE PACKING



HOW TO APPLY

HOW TO USE

- Surface to be treated should be dry and free from all dirt, oil, debris and all other contamination which could prevent penetration.
- Apply one coat of Trubuild WRP 777 by brush and leave the same to dry for next 24 hrs.
- Apply second coat wet on wet to improve the penetration and performance and again leave the same to dry for the next 24 hrs.

RESTRICTIONS ON USE

- Trubuild WRP 777 should not be diluted further as it will reduce its effectiveness.

TRUBUILD WRP 777

Water Repellent



TECHNICAL DATA SHEET
VER NO. 1.1

TECHNICAL DETAILS

PROPERTIES	STANDARD	RESULTS
Appearance		Transparent
Colour		Colorless
Density (gm/cc)	ASTM D 1475-2013	1.01 ± 0.01
% active ingredient		2.5-3.5%
Surface dry time, minutes		20-30
Water repellence	IS: 12027: 1987	Repels water in bead form
Water absorption %	IS: 12027: 1987	Pass <3%

HANDLING

Mandatory and recommended industrial hygiene procedures should be followed whenever our products are being handled and processed. For additional information please consult the corresponding product data sheets and the brochure "hygienic precautions for handling plastics products".

STORAGE

Product should be stored in a dry place in its original, properly closed container at a temperature between 2-40°C. Partially emptied containers should be closed immediately.

COVERAGE

- On porous substrate: 5-6 sqmt./L/coat
- On low porous substrate: 7-8 sqmt./L/coat

Note- Coverage depends on the porosity of the surface

SHELF LIFE

24 months (storage temp 2-40°C)

DISCLAIMER: This technical data sheet replaces all previous versions of it from the immediate effect. The information, and, in particular, the recommendations relating to the application and end-use of Astral Ltd, construction chemical products, are given in good faith based on our knowledge and experience of the products when properly stored, handled and applied under suitable favourable conditions in accordance with application instructions recommended in product technical data sheet. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. For the products on which company is offering warranty, please refer to warranty document to know entire terms and conditions. The same can be availed on request or from company website. The values mentioned in the above tables in technical data sheet are obtained in controlled lab conditions when tested properly by competent laboratory. Tolerance up to five to ten percentage on the lower side from the above values are allowable. Astral Ltd. reserves the right to change the properties of its products without notice. The end user of the product must test the product's suitability for the intended application and purpose. Astral Ltd will not bear any responsibilities on the product failure if it is wrongly positioned or if improper application methodology is adopted by the user or the applicator. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local product technical data sheet for the product concerned, copies of which will be supplied on request. No freedom from any patent owned by Seller or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, customer is responsible for determining whether products and the information in this document are appropriate for the customer's use and for ensuring that the customer's workplace, and disposal practices are in compliance with applicable laws and other governmental enactments.



ASTRAL LIMITED

CIN: U24295GJ2009PLC058120

Registered Office: 207/1, 'Astral House', B/h Rajpath Club, Off S.G. Highway, Ahmedabad-380059, Gujarat, India.

P: +91 79 6621 2000 | F: +91 79 6621 2121

E-mail: customercare@astraladhesives.com Website: www.trubuild.in