

**TRU
BUILD™**
TILING & GROUTING SOLUTIONS


 **ASTRAL®**

CELEBRATING
25 YEARS
OF TRUST &
INNOVATION



**COMPREHENSIVE
RANGE OF TILING AND
GROUTING SOLUTIONS**

THE 25 YEAR ASTRAL JOURNEY





Astral TruBuild: Elevating Excellence in Indian Construction Sector

Innovation drives Astral's journey in the Building Materials industry. A symbol of trust, we have contributed to the real estate sector in the past 25 years with our pioneering products and services.

TruBuild, an Astral legacy, specializes in the waterproofing, tiling, and grouting sectors

Water seepage harms the structure of any construction as it leads to mold formation and internal damage. As a result, increasing cost. Moreover, below-par tile solutions result in gaps, leakage, compromising appeal and hygiene. Our comprehensive product range can overcome both problems and ensure safety and aesthetics.

Astral TruBuild: Your Quality Symbol

From waterproofing to tiling, our products are truly built to perform. Our advanced waterproofing range ensures endurance and safeguards surfaces at every part of the construction, while our tile adhesives and grouting solutions offer firm bonds and beauty.

For structures that stand the test of time, choose Astral TruBuild.

Contents

PRODUCT CLASSIFICATION	05
INNOVATIONS IN TILE FIXING PROCESS	06
1 BHK HOUSE	07
PREMIUM BUNGLOW	08
• TRUBUILD TA 110 Grey.....	09
• TRUBUILD TA 220 Grey.....	10
• TRUBUILD TA 220 Plus Grey.....	11
• TRUBUILD TA 220 Plus White.....	12
• TRUBUILD TA 330 Grey.....	13
• TRUBUILD TA 330 White.....	14
• TRUBUILD TA 660 Grey.....	15
• TRUBUILD TA 660 White	16
• TRUBUILD EFX 666	17
• TRUBUILD Stain Free Epoxy Grout	18
• TRUBUILD Tile Grout	19
TRUBUILD SFEG SHADE CARD	20

PRODUCT CLASSIFICATION



TA 110
TYPE 1



TA 220
TYPE 1 (T1T)



TA 220 PLUS | GREY & WHITE
TYPE 2 (T2T)



TA 220 PLUS | GREY & WHITE
TYPE 2 (T2T)



TA 330 | GREY & WHITE
TYPE 3 (T3T)



TA 330 | GREY & WHITE
TYPE 3 (T3T)



TA 660 | GREY & WHITE
TYPE 4 (T4TS1)



TA 660 | GREY & WHITE
TYPE 4 (T4TS1)



EFX 666
TYPE 5 (T5S2)



STAIN FREE EPOXY GROUT
(SFEG)




TILE GROUT

INNOVATIONS IN TILE FIXING PROCESS SPEARHEADED BY DESIGN EXPERTS

ADVANCEMENT IN TECHNICAL STANDARDS

OLD		NEW				
INDIAN STANDARDS IS15477:2004		INDIAN STANDARDS IS15477:2019				
		Type I (T1)	Type II (T2)	Type III (T3)	Type IV (T4)	Type V (T5)
Standards evolved as per new trends in tiles and applications						
		EN 12004/ ISO 13007 STANDARDS		C/R 1/2 T E S1/2		
Type I (T1)	Type II (T2)	TYPE	CLASSES	SPECIAL CHARACTERISTICS		
		C = Cementitious	1 = Normal performance	T = Slip-resistant		
		R = Resinous	2 = Improved performance	E = Extended open time		
				S1 = Deformable (2.5-5 mm)		
				S2 = Highly deformable (> 5 mm)		

1 BHK HOUSE



PREMIUM BUNGLOW

7

TRUBUILD STAIN FREE EPOXY GROUT GROUTING

Bathroom Floor

5

TRUBUILD TA 660 WHITE (TILE SIZE: 6FT X 8FT)*

Bathroom Wall

6

TRUBUILD TA 660 WHITE (TILE SIZE: 6FT X 8FT)*

Bathroom Floor



2

TRUBUILD STAIN FREE EPOXY GROUT

Epoxy Grouting in Exterior Balcony/Lawn

4

TRUBUILD TA 660 WHITE Glass Mosaic Tiles in Swimming Pool

3

TRUBUILD TA 660 WHITE (TILES/STONE SIZE: 6FT X 8FT)*

(A) Large Format Tiles in Drawing Room

(B) Marble Flooring in Dining Room


1

TRUBUILD EFX 666

Natural Stone Fixing (Exterior)

TRUBUILD TA 110 GREY

TILE ADHESIVE



COLOUR




WATER
MIXING



SET TIME



INDOOR



20 kg



ADHESIVE

USAGE DETAILS

TYPE OF USAGE	AREA OF USAGE	TYPE OF SUBSTRATE	TYPE OF TILES	REGION (DRY/WET)	MAXIMUM SIZE OF TILES CAN BE FIXED	MAXIMUM HEIGHT OF WALL TO FIX TILES
Floor	Interior only	Cementitious substrate	Ceramic, Non-Vitrified, Porous Stones	Dry	Small Format Tiles	NA

TECHNICAL DETAILS

CONFORMS TO 15477 - 2004	PACK SIZES	COLOURS AVAILABLE	COVERAGE	MINIMUM BED THICKNESS REQUIRED	TENSILE ADHESION (N)	SHEAR ADHESION (kN)
Type-1	20 kg	Grey	Approx. 50-65 sq.ft/ 20 kg	3 mm	Dry condition 1020	Dry condition 8

TRUBUILD TA 220 GREY

TILE ADHESIVE



COLOUR




WATER
MIXING



SET TIME



INDOOR



ADHESIVE



APPLICATION

20 kg

USAGE DETAILS

TYPE OF USAGE	AREA OF USAGE	TYPE OF SUBSTRATE	TYPE OF TILES	REGION (DRY/WET)	MAXIMUM SIZE OF TILES CAN BE FIXED	MAXIMUM HEIGHT OF WALL TO FIX TILES
Floor	Interior only	Cementitious substrate	Ceramic, clay, terracotta, brick, quarry tiles, vitrified/fully vitrified & stone tiles etc.	Dry	Large Format Tiles	NA
Wall	Interior only	Cementitious substrate	Ceramic, clay, terracotta, brick, quarry tiles, vitrified/fully vitrified & stone tiles etc.	Dry	Small Format Tiles	Upto 8 Feet

TECHNICAL DETAILS

CONFORMS TO IS: 15477:2019	PACK SIZES	COLOURS AVAILABLE	COVERAGE	MINIMUM BED THICKNESS REQUIRED	TENSILE ADHESION (N/mm ²)	SHEAR ADHESION (N/mm ²)
Type-1T	20 kg	Grey	Approx. 50-65 sq. ft./20 kg	3 mm	Dry condition -0.62	Dry condition -1.07

TRUBUILD TA 220 PLUS GREY

TILE ADHESIVE

Grey

COLOUR

4.2-4.4 L
per bag

WATER
MIXING

24hrs

SET TIME



INDOOR &
OUTDOOR



Type 2-T2T(E)
ADHESIVE

20 kg

USAGE DETAILS

TYPE OF USAGE	AREA OF USAGE	TYPE OF SUBSTRATE	TYPE OF TILES	REGION (DRY/WET)	MAXIMUM SIZE OF TILES CAN BE FIXED	MAXIMUM HEIGHT OF WALL TO FIX TILES
Floor	Interior/ Exterior under shade	Cementitious substrate	Ceramic, clay, terracotta, brick, quarry tiles, large format vitrified/ fully vitrified tiles, glass mosaic tiles, terrazzo, all stones	Dry and Wet	Large Format Tiles	NA
Wall	Interior only	Cementitious substrate	Ceramic, clay, terracotta, brick, quarry tiles, large format vitrified/ fully vitrified tiles, glass mosaic tiles, terrazzo, all stones	Dry and Wet	Large Format Tiles	Upto 8 Feet

TECHNICAL DETAILS

CONFORMS TO IS: 15477:2019	PACK SIZES	COLOURS AVAILABLE	COVERAGE	MINIMUM BED THICKNESS REQUIRED	TENSILE ADHESION (N/mm ²)	SHEAR ADHESION (N/mm ²)
Type-2 T	20 kg	Grey	Approx. 50-65 sq. ft./ 20 kg	3 mm	Dry condition-1.17, Wet condition-1.08	Dry condition-1.39, Wet condition-1.11, Heat condition-1.42

TRUBUILD TA 220 PLUS WHITE

TILE ADHESIVE



COLOUR

4.4-4.6 L
per bag

WATER
MIXING



SET TIME



INDOOR &
OUTDOOR



ADHESIVE

20 kg

USAGE DETAILS

TYPE OF USAGE	AREA OF USAGE	TYPE OF SUBSTRATE	TYPE OF TILES	REGION (DRY/WET)	MAXIMUM SIZE OF TILES CAN BE FIXED	MAXIMUM HEIGHT OF WALL TO FIX TILES
Floor	Interior / Exterior under shade	Cementitious substrate	Ceramic, clay, terracotta, brick, quarry tiles, large format vitrified/ fully vitrified tiles, glass mosaic tiles, terrazzo, all stones	Dry and Wet	Large Format Tiles	NA
Wall	Interior only	Cementitious substrate	Ceramic, clay, terracotta, brick, quarry tiles, large format vitrified/ fully vitrified tiles, glass mosaic tiles, terrazzo, all stones	Dry and Wet	Large Format Tiles	Upto 8 Feet

TECHNICAL DETAILS

CONFORMS TO IS: 15477:2019	PACK SIZES	COLOURS AVAILABLE	COVERAGE	MINIMUM BED THICKNESS REQUIRED	TENSILE ADHESION (N/mm ²)	SHEAR ADHESION (N/mm ²)
Type-2 T	20 kg	White	Approx. 50-65 sq. ft./ 20 kg	3 mm	Dry condition-1.22, Wet condition -1.12	Dry condition -1.42, Wet condition-1.18, Heat condition-1.46

TRUBUILD TA 330 GREY

TILE ADHESIVE



Grey

COLOUR

4.2-4.4 L
per bag

WATER
MIXING

24hrs

SET TIME



INDOOR &
OUTDOOR

TA 330
TILE ADHESIVE

20 kg

Grey

Colour

4.2-4.4 L
per bag

Water
Mixing

24hrs

Set Time

Type-T3T(E)

Adhesive



Indoor &
Outdoor

Type - T3T(E)

ADHESIVE

USAGE DETAILS

TYPE OF USAGE	AREA OF USAGE	TYPE OF SUBSTRATE	TYPE OF TILES	REGION (DRY/WET)	MAXIMUM SIZE OF TILES CAN BE FIXED	MAXIMUM HEIGHT OF WALL TO FIX TILES
Floor	Interior / Exterior	Cementitious substrate	Ceramic, clay, terracotta, brick, quarry tiles, vitrified/fully vitrified tiles, glass mosaic tiles, terrazzo, basalt, porcelain tiles & other stones	Dry and Wet	Large Format Tiles	NA
Wall	Interior / Exterior	Cementitious substrate	Ceramic, clay, terracotta, brick, quarry tiles, vitrified/fully vitrified tiles, glass mosaic tiles, terrazzo, basalt, porcelain tiles & other stones	Dry and Wet	Large Format Tiles	Upto 10 Feet

TECHNICAL DETAILS

CONFORMS TO IS: 15477:2019	PACK SIZES	COLOURS AVAILABLE	COVERAGE	MINIMUM BED THICKNESS REQUIRED	TENSILE ADHESION (N/mm ²)	SHEAR ADHESION (N/mm ²)
Type-3 T	20 kg	Grey	Approx. 50-65 sq. ft./ 20 kg	3 mm	Dry condition-1.56, Wet condition -1.21	Dry condition -1.64, Wet condition-1.19, Heat condition-1.61

TRUBUILD TA 330 WHITE

TILE ADHESIVE



COLOUR

4.2-4.4 L
per bag

WATER
MIXING



SET TIME



INDOOR &
OUTDOOR



ADHESIVE

20 kg

USAGE DETAILS

TYPE OF USAGE	AREA OF USAGE	TYPE OF SUBSTRATE	TYPE OF TILES	REGION (DRY/WET)	MAXIMUM SIZE OF TILES CAN BE FIXED	MAXIMUM HEIGHT OF WALL TO FIX TILES
Floor	Interior / Exterior	Cementitious substrate	Ceramic, clay, terracotta, brick, quarry tiles, vitrified/fully vitrified tiles, glass mosaic tiles, terrazzo, basalt, porcelain tiles & other stones	Dry and Wet	Large Format Tiles	NA
Wall	Interior / Exterior	Cementitious substrate	Ceramic, clay, terracotta, brick, quarry tiles, vitrified/fully vitrified tiles, glass mosaic tiles, terrazzo, basalt, porcelain tiles & other stones	Dry and Wet	Large Format Tiles	Upto 10 Feet

TECHNICAL DETAILS

CONFORMS TO IS: 15477:2019	PACK SIZES	COLOURS AVAILABLE	COVERAGE	MINIMUM BED THICKNESS REQUIRED	TENSILE ADHESION (N/mm ²)	SHEAR ADHESION (N/mm ²)
Type-3 T	20 kg	White	Approx. 50-65 sq. ft./ 20 kg	3 mm	Dry condition-1.74, Wet condition -1.32	Dry condition -1.71, Wet condition-1.36, Heat condition-1.75

TRUBUILD TA 660 GREY

TILE ADHESIVE

Grey

COLOUR

4.2-4.4 L
per bag

WATER
MIXING

24hrs

SET TIME



INDOOR &
OUTDOOR



Type-T4TS1(E)

ADHESIVE

20 kg

USAGE DETAILS

TYPE OF USAGE	AREA OF USAGE	TYPE OF SUBSTRATE	TYPE OF TILES	REGION (DRY/WET)	MAXIMUM SIZE OF TILES CAN BE FIXED	MAXIMUM HEIGHT OF WALL TO FIX TILES
Floor	Interior / Exterior	Cementitious substrate	Ceramic, clay, terracotta, brick, quarry tiles, vitrified/fully vitrified tiles, glass mosaic tiles, terrazzo, basalt, porcelain tiles & other stones	Dry and Wet	Large Format Tiles	NA
Wall	Interior / Exterior	Cementitious substrate	Ceramic, clay, terracotta, brick, quarry tiles, vitrified/fully vitrified tiles, glass mosaic tiles, terrazzo, basalt, porcelain tiles & other stones	Dry and Wet	Large Format Tiles	10 Feet and Above

TECHNICAL DETAILS

CONFORMS TO IS: 15477:2019	PACK SIZES	COLOURS AVAILABLE	COVERAGE	MINIMUM BED THICKNESS REQUIRED	TENSILE ADHESION (N/mm ²)	SHEAR ADHESION (N/mm ²)
Type-4 T S1	20 kg	Grey	Approx. 50-65 sq. ft./ 20 kg	3 mm	Dry condition-1.59, Wet condition-1.26	Dry condition-1.69, Wet condition-1.29, Heat condition-1.59

TRUBUILD TA 660 WHITE

TILE ADHESIVE



COLOUR



WATER
MIXING



SET TIME



INDOOR &
OUTDOOR



ADHESIVE

20 kg

USAGE DETAILS

TYPE OF USAGE	AREA OF USAGE	TYPE OF SUBSTRATE	TYPE OF TILES	REGION (DRY/WET)	MAXIMUM SIZE OF TILES CAN BE FIXED	MAXIMUM HEIGHT OF WALL TO FIX TILES
Floor	Interior / Exterior	Cementitious substrate	Ceramic, clay, terracotta, brick, quarry tiles, vitrified/fully vitrified tiles, glass mosaic tiles, terrazzo, basalt, porcelain tiles & other stones	Dry and Wet	Large Format Tiles	NA
Wall	Interior / Exterior	Cementitious substrate	Ceramic, clay, terracotta, brick, quarry tiles, vitrified/fully vitrified tiles, glass mosaic tiles, terrazzo, basalt, porcelain tiles & other stones	Dry and Wet	Large Format Tiles	10 Feet and Above

TECHNICAL DETAILS

CONFORMS TO IS: 15477:2019	PACK SIZES	COLOURS AVAILABLE	COVERAGE	MINIMUM BED THICKNESS REQUIRED	TENSILE ADHESION (N/mm ²)	SHEAR ADHESION (N/mm ²)
Type-4 T S1	20 kg	White	Approx. 50-65 sq. ft./ 20 kg	3 mm	Dry condition-1.79, Wet condition-1.36	Dry condition-1.74, Wet condition-1.39, Heat condition-1.78

TRUBUILD EFX666

EPOXY ADHESIVE



HIGH
COVERAGE



SHATTER-
PROOF



IDEAL FOR
DRYWALLS, METAL
& PLYWOOD



VERSATILE



INTERIOR & EXTERIOR
APPLICATIONS

USAGE DETAILS

TYPE OF USAGE	AREA OF USAGE	TYPE OF SUBSTRATE	TYPE OF TILES	REGION (DRY/WET)	MAXIMUM SIZE OF TILES CAN BE FIXED	MAXIMUM HEIGHT OF WALL TO FIX TILES
Floor	Interior / Exterior	Metal, dry walls, wood, glass, cementitious surface like plaster, RCC etc.	Ceramic, procelein, marble, natural stone, clinker bricks, glass & ceramic mosaic, granite, recomposed materials & wood, metals, rubber and linoleum etc.	Dry and Wet	Very Large Format Tiles	NA
Wall	Interior / Exterior	Metal, dry walls, wood, glass, cementitious surface like plaster, RCC etc.	Ceramic, procelein, marble, natural stone, clinker bricks, glass & ceramic mosaic, granite, recomposed materials & wood, metals, rubber and linoleum etc.	Dry and Wet	Very Large Format Tiles	Any Height

TECHNICAL DETAILS

CONFORMS TO IS: 15477:2019 EN: 12004:2017	PACK SIZES	COLOURS AVAILABLE	COVERAGE	MINIMUM BED THICKNESS REQUIRED	TENSILE ADHESION (N/mm ²)	SHEAR ADHESION (N/mm ²)
Type-5 T S2 & R2T	4 kg	White	Approx. 2-4 kg/m ²	1.5 mm, 3mm	Dry condition-2.5	Dry condition-6, Wet condition-5, Heat condition-6

TRUBUILD STAIN FREE EPOXY GROUT

EPOXY GROUT



STAIN-FREE &
EASILY CLEANED



RESISTANT TO MILD
CHEMICALS & ACIDS



NON-CRACKING
OR POWDERING



AVAILABLE IN A RANGE
OF ATTRACTIVE COLORS

USAGE DETAILS

TYPE OF USAGE	AREA OF USAGE	TYPE OF SUBSTRATE	TYPE OF TILES/STONES	REGION (DRY/WET)	MAXIMUM WIDTH OF TILE JOINT CAN BE FILLED	CAN BE USED IN VIBRATION AREA
Floor	Kitchen, bathrooms, swimming pools, wash area, living rooms, parking spaces etc.	Ceramic tile, vitrified tiles and stones joints etc	Ceramic tile, vitrified tiles and stones joints etc	Dry and Wet	12 mm	NA

TECHNICAL DETAILS

SPECIFICATION FOLLOWED	PACK SIZES	COLOURS AVAILABLE	MIXING RATIO FOR MATTE FINISH	MIXING RATIO FOR GLOSSY FINISH	COVERAGE	TENSILE ADHESION AS PER ISO 13007 (N/mm ²)
ANSI 118.3:1999/ EN 13888:2009 & ISO 13007:2015	5 kg & 1 kg	36 Vibrant Shades	For 1 kg pack: Resin-180 gm, Hardener-70 gm, Filler-750 gm. For 5 kg pack: Resin-900 gm, Hardener-350 gm, Filler-3750 gm	For 1 kg pack: Resin-180 gm, Hardener-70 gm, Filler-550 gm. For 5 kg pack: Resin-900 gm, Hardener-350 gm, Filler-2750 gm	Depends upon the width of tile joints & size of tiles	Dry condition-65.2

TRUBUILD TILE GROUT

POLYMERIC CEMENT
BASED TILE GROUT

2.5:1

WATER MIXING
RATIO (BY WEIGHT)



ECONOMICAL



UNIFORM
COLOUR



INDOOR &
OUTDOOR



USAGE DETAILS



















TYPE OF USAGE	AREA OF USAGE	TYPE OF SUBSTRATE	TYPE OF TILES/STONES	REGION (DRY/WET)	CAN BE USED IN VIBRATION AREA
Floor & wall	Cementitious tile grout	Ceramic tiles, vitrified tiles and stones etc.	Ceramic tiles, vitrified tiles and stones etc.	Dry and Wet	NA

TECHNICAL DETAILS

PACK SIZES	COLOURS AVAILABLE	COVERAGE	MIXING RATIO
500 gm box, 1 kg box & 1 kg pouch	In various colours	Approx. 2.52 kg/ m ² for tile dimension length 25 mm, breadth 25 mm, thickness of tiles 6 mm & width of groove size 3 mm	2.5:1, by weight (powder to water)

STAIN FREE EPOXY GROUT
MATT & GLOSSY
FINISH

SHADE OPTIONS

COLOR NAME	COLOUR TONE
WHITE	
ANTIQUE WHITE	
GREY	
PLATINUM GREY	
STERLING SILVER	
CEMENT	
SANDSTONE	
MOCHA	
COPPER BROWN	
MUSHROOM	
MOLTEN BRONZE	
YELLOW	
YELLOW ROSE (BASIC)	
CHROME YELLOW	
ENGRASS	
MILD GREEN	
MENTA	
WHISPERING GREEN	

COLOR NAME	COLOUR TONE
LIGHT GREEN	
SETERN	
ALPINO	
DARK GREEN	
DEEP LINE	
BABY PINK	
BURGANDY	
METAAL	
RED	
TERRA RED	
BLUE	
ALPINE BLUE	
DEEP DESIRE	
DARK BLUE	
PURPLE RAIN	
FANCY COCOA	
RAVEN	
BLACK	



Trubuild Stain Free Epoxy Tile Grout is a 3 component pre-packed epoxy grout specially designed for grouting of ceramic tiles, vitrified tiles and stones where staining is expected. It provides a stain-free, chemical resistant, hard wearing tile joint.

Surface Preparation

1. Remove dust, oil, debris & sealer from the joints with the help of wire brush or air blower.
2. Clean the tile surface with a damp sponge to remove dirt, dust, adhesive & stains.

How to Mix

1. Take Part-A & Part-B in a suitable container & mix well with a trowel or a slow drill mixer.
2. Add Part-C powder slowly to get uniform consistency. Mix till workable stiffness is formed.
3. Use a hard rubber grout float to compact grout into joints, ensuring that they are completely filled.
4. Work in small areas and remove excess materials from tile surface. Strike off excess materials diagonally to the grout lines.
5. Plug open-ended joints with the stiffer mix to prevent any slumping of the grout.

Coverage

TILE DIMENSION (mm)			CONSUMPTION OF EPOXY BASED TILE GROUT IN (kg/m ²)								
L(mm)	B(mm)	T(mm)	MIX DENSITY OF TILE GROUT->1.6 kg/litre								
			JOINT SIZE - J(mm)								
			2 mm	3 mm	4 mm	5 mm	6 mm	8 mm	10 mm	12 mm	
25	25	6	1.54	2.30	3.07	3.84	4.61	6.14	7.68	9.22	
25	50	6	1.15	1.73	2.30	2.88	3.46	4.61	5.76	6.91	
50	50	6	0.77	1.15	1.54	1.92	2.30	3.07	3.84	4.61	
100	100	6	0.38	0.58	0.77	0.96	1.15	1.54	1.92	2.30	
100	100	10	0.64	0.96	1.28	1.60	1.92	2.56	3.20	3.84	
300	200	6	0.16	0.24	0.32	0.40	0.48	0.64	0.80	0.96	
300	300	6	0.13	0.19	0.26	0.32	0.38	0.51	0.64	0.77	
450	300	6	0.11	0.16	0.21	0.27	0.32	0.43	0.53	0.64	
600	300	6	0.10	0.14	0.19	0.24	0.29	0.38	0.48	0.58	
600	600	8	0.09	0.13	0.17	0.21	0.26	0.34	0.43	0.51	
800	800	8	0.06	0.10	0.13	0.16	0.19	0.26	0.32	0.38	
1000	1000	10	0.06	0.10	0.13	0.16	0.19	0.26	0.32	0.38	
1200	600	10	0.08	0.12	0.16	0.20	0.24	0.32	0.40	0.48	
1200	800	10	0.07	0.10	0.13	0.17	0.20	0.27	0.33	0.40	
1200	1200	12	0.06	0.10	0.13	0.16	0.19	0.26	0.32	0.38	
1600	800	12	0.07	0.11	0.14	0.18	0.22	0.29	0.36	0.43	
1800	1200	12	0.05	0.08	0.11	0.13	0.16	0.21	0.27	0.32	

The quantities shown are approximate and are given for estimating purposes only. Actual job site coverage may vary from site to site.

Note: It is always good practice when calculating coverage to allow for 10% additional, material for waste and spillage.

TIP TIP NAHI

TRU BUILD

ADVANCED WATERPROOFING TILING & GROUTING SOLUTIONS

Integral

Repair & WP Polymers

Crack Filling

Terrace & Wall Coating

Polyurethane

2K Cementitious

Tile Grouts

Tile Adhesives

Sealants

Clearcoats

Epoxy Coatings

Mortars

ASTRAL TRU BUILD™



**THE ULTIMATE
TILING & GROUTING
RANGE**



Closer to you

VISIT US AT

www.wecare.astraladhesives.com



Scan the QR to download
the Tiling Brochure



ASTRAL LIMITED

HEAD OFFICE

207/1, Astral House, B/H
Rajpath Club, Off. S.G. Highway,
Ahmedabad-380059, Gujarat
+91-79-66212000

CORPORATE OFFICE

Office No. 9A, 9th Floor,
Krishna Tower, 15/63, Civil
Lines, Kanpur-208021, UP
+91-512-6670400/ 2331646

MUMBAI OFFICE:

C-615/616, C-Wing, Atrium, Chakala,
Andheri-Kurla Road, Andheri (East),
Mumbai-400 059, Maharashtra,
India.+91-9167216887

 customercare@astraladhesives.com

 +91 7311103331

 www.trubuild.in